

## Manual plastic strapping tools

---



### Characteristics

---

Strapping qualities:		Polypropylene (PP) and Polyester (PET)
Strapping dimensions:	widths	11.0 – 13.0 mm / ½"
	thicknesses	0.40 – 0.90 mm / .016 - .035"
Weights:		3.3 kg / 7.3 lbs without suspension 3.4 kg / 7.5 lbs with suspension
Average seal strength:		approx. 70 %
Type of joint:		Joint with special seals
Suspension (Optional):		bolt and grip ball for horizontal applications; have to be ordered separately

### Advantages

---

- Handy light weight tensioning and sealing tool to strap flat packages (i.e. pallets, bales, crates, cases, various packages) using plastic strapping
- A reliable, robust and service – friendly tool
- The windless tensioning system allows very high strap tension
- Special serrated seals and the patented sealing force balance system guarantee a very high seal joint efficiency
- The sealing handle is always operated until it hits the stop – thus the seal efficiency of all joints is high and balanced

**Chart of types model P403**

---

Item No.	Model	Width		Thicknesses	
		mm	inch	mm	inch
43.0403	P403/11-13/0.40-0.90	11-13	1/2"	0.40-0.90	.016-.035

**Seals**

---

Item No.	Model	Width		Contents of carton in pcs.	Weight	
		mm	inch		kg	lbs
41.5081	P403/13	11-13	1/2"	1000	6.5	14.3

**Accessories**

---

P40.2046 Handle for horizontal applications  
(Grip ball and bolt)